



...mobil mit Batterien



TRIMAXX[®]
energetic

TRIMAXX energetic

Starter batteries and batteries for railway applications

Designation	Voltage V	Capacity Ah (C20)	Cold test current A (EN)	Design	Dimensions in mm (L x W x H)	Circuit	End pole type	Base- board	Weight kg	DIN No.
TRIMAXX Professional TP										
TP 47 Pro	12	47	420	Start	207 x 175 x 175	0	1	B13	11.4	54459
TP 52 Pro	12	52	450	Start	207 x 175 x 190	0	1	B13	12.1	54464
TP 60 Pro	12	60	530	Start	242 x 175 x 175	0	1	B13	13.7	55559
TP 64 Pro	12	64	550	Start	242 x 175 x 190	0	1	B13	14.5	56219
TP 72 Pro	12	72	630	Start	278 x 175 x 175	0	1	B13	15.5	56420
TP 75 Pro	12	75	680	Start	278 x 175 x 190	0	1	B13	17.4	57412
TP 85 Pro	12	85	780	Start	315 x 175 x 175	0	1	B13	19.3	57539
TP 100 Pro	12	100	900	Start	353 x 175 x 190	0	1	B13	22.9	60044
TRIMAXX energetic wet TREW										
TREW12V125	12	125	1100	HD	286 x 269 x 230	2	1	B00	34.5	62523
TREW12V140	12	140	760	HD	513 x 189 x 215	3	1	B00	35.0	64020
TREW12V180	12	180	950	SHD	512 x 222 x 215	3	1	B00	44.0	68032
TREW12V200	12	200	1050	SHD	517 x 273 x 242	3	1	B00	54.0	70038
TREW12V225	12	225	1050	SHD	517 x 273 x 235	3	1	B00	59.0	72511
TRIMAXX Premium Truck										
TPT 140 SHD	12	140	800	SHD	513 x 189 x 220	3	1	-	36.6	64035
TPT 180 SHD	12	180	1000	SHD	513 x 223 x 220	3	1	-	45.7	68032
TPT 225 SHD	12	225	1150	SHD	518 x 274 x 240	3	1	-	59.6	72511



TRIMAXX Professional TP

The high-performance battery for sophisticated applications

- Up to 30 % increased cold starting capacity
- Calcium/Calcium/Silver technology
- Absolutely maintenance-free
- High-end quality
- Magic Eye for state of charge control
- Release for increased charging voltage of 14.8 Volt
- Fulfills the requirements for the 180° rollover test



TRIMAXX energetic wet TREW

The durable battery

- Hybrid Antimony/Calcium technology
- Maintenance-free
- Original equipment manufacturer (OEM) quality
- For starting and cyclical applications
- In HD and SHD design
- Screw connections located at the top



TRIMAXX Premium Truck

The power package with particularly robust design

- Advanced Calcium/Calcium technology
- Absolutely maintenance-free
- Original equipment manufacturer (OEM) quality
- Increased starting power



GW Batterien GmbH
Emilienstraße 24a
D - 08056 Zwickau
Tel: +49 (0)375 211855-0
Fax: +49 (0)375 211855-55
info@gwbatt.de
www.gwbatt.de

Dated 09/2020
subjects to modifications

